



## GraffStop – Clear (Matt or Gloss)

### Technical Data Sheet

- **GraffStop is a permanent non-sacrificial coating giving excellent protection against graffiti and fly poster attack, allowing graffiti to be easily removed with the use of water/detergent.**
- **GraffStop can be used on porous and non porous surfaces.**

#### INSTRUCTIONS FOR USE

##### Material

**GraffStop** is used for protecting surfaces to allow easy removal of graffiti.

Can also be used on porous and non-porous substrates, painted and metal surfaces.

Some surfaces will need the use of a primer prior to application of GraffStop.

##### Surface Preparation:

All surfaces must be clean and dry.

Remove any soiling by power washing etc.

Any soiling/graffiti on painted surfaces must either be fully removed or painted over using good quality masonry exterior paint prior to application.

Non Darkening Sealer/Primer should be applied prior to application on all non-painted sandstone or brick surfaces.

##### Application:

Apply by brush, roller or airless spray.

##### Coverage:

6-10sqm/litre depending on porosity of substrate.

##### Drying Time:

Recoating time: 2-4 hours depending on conditions.

Completely dry: 6-8 hours depending on conditions.

##### Graffiti Removal:

Removal with water.

Ideal cleaning is via a pressure washer hot or cold. In stubborn areas mild detergent is sometimes needed. For small areas a bucket of water, sponge/nail brush should be sufficient

#### NOTE WHEN REMOVING GRAFFITI – Damage can occur to the Anti-Graffiti System and the Substrate if:

- The power used is above 1000 psi.
- A turbo or pencil tip is used.
- The tip touches or gets too close to the surface.
- Too high temperature is used.
- The Anti Graffiti Coating is damaged or incomplete allowing the pressure washer to get behind it and blow the coating off.

Note: Strong solvent cleaners should not be used with the Anti Graffiti Coating as they may damage the system.

##### Guidelines

- ✓ Supplied in 5 litre tins
- ✓ Clear Liquid
- ✓ VOC 470g/l
- ✓ 47-53% volume solids
- ✓ Contains ALKANES & METHYL-0-0'00"- BUTAN-2-ONE-TRIOXIMOSILANE

##### Precautions

Gloves, Safety glasses to be used in case of splashes.

##### Storage

Store at room temperature in original closed container.

##### Shelf life

Approximately 12 months in unopened container.

##### Marking

Classified as Harmful.

Not classified as dangerous.

Not classified in **ADR** or **IMDG**.